



**800**  
**PERMANENT**  
**ASPHALT REPAIR**  
By Imco ®

**“READY TO USE”**

**“NO PRIMER REQUIRED”**

**DESCRIPTION**

Our unique formulation is designed so that you can achieve optimum performance all year long in any weather conditions with one product.

**USES**

Permanently repair any holes in asphalt or concrete, in all types of weather even wet or freezing or extreme heat conditions.

**FEATURES**

- Unique formulation premixed and ready to use. Permanent repair = Cost effectiveness
- Convenient packaging, for all repairs, 50 pound bags, 5 gallon pails and 55 gallon drums
- Easy 3 step repair
- Backed by Imco's® strict quality control
- Testing at independent laboratories

**TECHNICAL DATA**

Asphalt Content:	ASTM D2172-92	5.2%
Static Stripping:	ASTM D1664-80	95-100%
Kinetic Stripping:	OPSS 1153-02-01	95%

**PREPARATION**

Clean out any loose chunks or debris using a stiff broom or blower to achieve a sound surface to bond to.

**APPLICATION**

Place **PERMANENT ASPHALT REPAIR** by Imco® in hole, in layers of 3 inches at a time. Compact PAR 800 with a tamper, roller or by driving over it. Repeat until the hole is filled to the desired thickness. To speed set up time, reduce tacky surface, dust with sand or cement. **“READY TO DRIVE ON.”**

**Q & A**

- Shelf life- one year
- Seasonal grades- NO
- One all purpose grade
- Set up time- Immediate
- Coverage-10 pounds per square foot at one at 1 inch deep, 1.4 tons per cubic yard

**SAFETY**

Please refer to MSDS at [www.imcotechnologies.com](http://www.imcotechnologies.com)

**WARRANTY DISCLAIMER**

The information herein is to assist customers in determining whether our products are suitable for their application. Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to the contents and suitability. We warrant that our products will meet our written specifications. Nothing herein shall constitute a warranty expressed or implied including any warranty of merchantability of fitness, nor is protection from any loss or patent to be inferred. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for