

# WATERPROOFING

## Barricure™

### Description

Barricure is an aqueous solution of special ingredients for curing Barriseal®-S and Barricoat®-S rubberized asphalt emulsions in spray application. Barricure is sprayed in tandem with Barriseal-S or Barricoat-S through spray equipment approved by CCW.

Barricure is used as a curative co-spray with Barriseal-S spray-applied air/vapor barrier membrane or Barricoat-S spray-applied waterproofing membrane. Barricure presents a chloride-free option when used instead of the standard calcium chloride solution co-spray in these applications.

### Features and Benefits

- Will not cause corrosion to adjacent or embedded metal components
- Suitable for use in systems where introduction of chlorides is forbidden
- Mess-free, easy dispense with pour-spout on pails
- Liquid concentrate mixes rapidly and easily with water in the equipment co-spray tank
- Specially formulated and provided by CCW for use with Barriseal and Barricoat spray-applied membranes

### Installation

CCW Barricure mixture ratio with water is 4:1.

Recommended Barricure Spray Tip Size:  
Graco XHD 627 or TP 6501-SS

### Warnings and Hazards

Caution: IRRITANT. Contains sodium salt of an organic acid mixture and calcium nitrate. May cause eye/ skin/ respiratory irritation. Refer to MSDS for important warnings and product information.

### Storage

Store above 40°F. Protect from direct sunlight. Keep from freezing. If product freezes, warm to room temperature and stir to re-dissolve solids.

### Packaging

| Product     | Size   |
|-------------|--|
| Barricure   | 5-gal plastic pail with pour spout; 59 lb per pail |
| Barriseal-S | 50-gal drums; 330-gallon totes                     |
| Barricoat-S | 50-gal drums; 330-gallon totes                     |

### Limited Warranty

Carlisle Coatings & Waterproofing Incorporated (Carlisle) warrants this product to be free of defects in workmanship and materials only at the time of shipment from our factory. If any Carlisle materials prove to contain manufacturing defects that substantially affect their performance, Carlisle will, at its option, replace the materials or refund its purchase price. This limited warranty is the only warranty extended by Carlisle with respect to its materials. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose. Carlisle specifically disclaims liability for any incidental, consequential, or other damages, including but not limited to, loss of profits or damages to a structure or its contents, arising under any theory of law whatsoever. The dollar value of Carlisle's liability and buyer's remedy under this limited warranty shall not exceed the purchase price of the Carlisle material in question.