

Material Name: CCW-702 LV

Product #: 316148

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name CCW-702 LV

Chemical Family Adhesive

Product Use Low VOC Adhesive

Restrictions on Use For industrial use only.

Manufacturer Information

Carlisle HVAC Products 900 Hensley Lane Wylie, TX 75098 www.carlislehvac.com MSDS Assistance – 972-442-6545 Technical Assistance – 888-229-2199 Customer Service – 888-229-0199

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Flammable Liquids - Category 2 Aspiration Hazard - Category 1 Acute Toxicity - Inhalation - Vapor - Category 4 Skin Corrosion/Irritation - Category 2 Serious Eye Damage/Eye Irritation - Category 2A Specific Target Organ Toxicity - Single Exposure - Category 1 (central nervous system) Specific Target Organ Toxicity - Single Exposure - Category 3 Specific Target Organ Toxicity - Repeated Exposure - Category 1 (central nervous system) Specific Target Organ Toxicity - Repeated Exposure - Category 2 (blood)

GHS Label Elements



Signal Word Danger



Material Name: CCW-702 LV

Product #: 316148

Hazard Statement(s) Highly flammable liquid and vapor May be fatal if swallowed and enters airways Harmful if inhaled Causes skin irritation Causes serious eye irritation Causes damage to organs May cause respiratory irritation. May cause drowsiness or dizziness Causes damage to organs through prolonged or repeated exposure May cause damage to organs through prolonged or repeated exposure

Precautionary Statement(s)

Prevention

Keep container tightly closed Keep away from heat/sparks/open flame/hot surfaces - No smoking Ground/Bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting equipment Take precautionary measures against static discharge Use only non-sparking tools Use only outdoors or in a well-ventilated area Wear protective gloves/protective clothing/eye protection/face protection Do not breathe dust/fume/gas/mist/vapours/spray Wash thoroughly after handling Do not eat, drink or smoke when using this product

Response

In case of fire: Use appropriate media to extinguish If exposed: Call a POISON CENTER or doctor/physician IF INHALED: Remove person to fresh air and keep comfortable for breathing Call a POISON CENTER or doctor if you feel unwell IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse IF SWALLOWED: Immediately call a POISON CENTER/doctor Do NOT induce vomiting Specific treatment (see label)

Storage

Store in a well-ventilated place. Keep container tightly closed Keep cool Store locked up

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

Statement of Unknown Toxicity

47.1415% of the mixture consists of ingredient(s) of unknown acute toxicity.



Material Name: CCW-702 LV

Other Hazards

No additional information available.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent		
108-88-3	Toluene	7-13		
67-64-1	Acetone	7-13		
Trade Secret	Petroleum hydrocarbon resin	10-30		
Mixture	Phthalo blue	0.1-1		
4477-79-6	C.I. Solvent Red 26	0.1-1		
540-88-5	tert-Butyl acetate	15-40		

Section 4 - FIRST AID MEASURES

Description of Necessary Measures

If exposed or concerned: Call a POISON CENTER or doctor/physician.

Inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

Skin

Remove contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation occurs, get medical advice/attention.

Eyes

Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Indication of any immediate medical attention and special treatment needed Treat symptomatically and supportively.

Most Important Symptoms/Effects

Acute

May be fatal if swallowed and enters airways. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. Causes damage to central nervous system. May cause respiratory irritation. May cause drowsiness or dizziness.



Material Name: CCW-702 LV

Delayed

Causes damage to organs through prolonged or repeated exposure: central nervous system, blood.

Note to Physicians

Contains toluene.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media Dry chemical, foam or carbon dioxide. Water may be ineffective.

Unsuitable Extinguishing Media

Do not use high-pressure water streams.

Special Hazards Arising from the Chemical

Highly flammable liquid and vapor. Vapors are heavier than air and may travel a considerable distance to a source of ignition and flashback.

Hazardous Combustion Products

Oxides of carbon, hydrocarbons. Fumes may be irritating.

Advice for firefighters

Keep away from heat/sparks/open flame/hot surfaces - No smoking. Ground/bond container and receiving equipment. Take action to prevent static discharges.

Fire Fighting Measures

Cool containers with water spray until well after the fire is out. Avoid inhalation of material or combustion by-products.

Special Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Remove all sources of ignition. Avoid breathing vapors. Ventilate affected area. Absorb with earth, sand or other non-combustible material and transfer to container. Dike for later disposal. Dispose in accordance with all applicable regulations.

Environmental Precautions

Avoid release to the environment.



Material Name: CCW-702 LV

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Keep container tightly closed. Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Ground/bond container and receiving equipment. Use explosion-proof equipment. Take precautionary measures against static discharge. Use non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid contact with eyes, skin and clothing. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. KEEP OUT OF REACH OF CHILDREN.

Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed Keep cool Store locked up Keep away from heat and ignition sources. Do not cut, puncture, or weld on or near this container. Empty containers may contain product residue.

Incompatible Materials

Strong acids, strong oxidizing agents

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Toluene	108-88-3				
ACGIH:	20 ppm TWA				
NIOSH:	100 ppm TWA; 375 mg/m3 TWA 150 ppm STEL; 560 mg/m3 STE				
	500 ppm IDLH				
Europe:	50 ppm TWA; 192 mg/m3 TWA 100 ppm STEL; 384 mg/m				
	Possibility of significant uptake through the skin				
OSHA (US):	200 ppm TWA	300 ppm Ceiling			
Mexico:	50 ppm TWA LMPE-PPT; 188 mg	/m3 TWA LMPE-PPT			
	Skin - potential for cutaneous absor	rption			
Acetone	67-64-1				



Material Name: CCW-702 LV

Product #: 316148

ACGIH:	250 ppm TWA	500 ppm STEL				
NIOSH:	250 ppm TWA; 590 mg/m3 TWA	2500 ppm IDLH (10% LEL)				
Europe:	500 ppm TWA; 1210 mg/m3 TWA					
OSHA (US):	1000 ppm TWA; 2400 mg/m3 TWA					
Mexico:	1000 ppm TWA LMPE-PPT; 2400 mg/m3 TWA LMPE-PPT					
	1260 ppm STEL [LMPE-CT]; 3000	0 mg/m3 STEL [LMPE-CT]				
Phthalo blue	Mixture					
Europe:	50 ppm TWA; 275 mg/m3 TWA	100 ppm STEL; 550 mg/m3 STEL				
	Possibility of significant uptake three	ough the skin				
tert-Butyl acetate	540-88-5					
ACGIH:	200 ppm TWA					
NIOSH:	200 ppm TWA; 950 mg/m3 TWA	1500 ppm IDLH (10% LEL)				
OSHA (US):	200 ppm TWA; 950 mg/m3 TWA					
Mexico:	200 ppm TWA LMPE-PPT; 950 m	g/m3 TWA LMPE-PPT				
	250 ppm STEL [LMPE-CT]; 1190 mg/m3 STEL [LMPE-CT]					

Biological limit value

There are no biological limit values for any of this product's components.

Engineering Controls

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear chemical safety goggles with a faceshield to protect against skin and eye contact when appropriate.

Skin Protection

Wear work clothes with long sleeves. Wear protective shoes. Recommended material: protective skin cream.

Respiratory Protection

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Glove Recommendations

Wear appropriate chemical resistant gloves.

Protective Materials

Provide an emergency eye wash fountain and quick drench shower in the immediate work area.



Material Name: CCW-702 LV

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	thick dark red liquid	Physical State	liquid
Odor	sweet,solvent	Color	dark red
Odor Threshold	Not available	рН	Not available
Melting Point	-95 °C (-139 °F)	Boiling Point	56 - 110 °C (133-231 °F)
Freezing point	Not available	Evaporation Rate	3.4
Boiling Point Range	Not available	Flammability (solid, gas)	Not available
Autoignition	465 °C (869 °F)	Flash Point	-17.8 °C (0 °F)
Lower Explosive Limit	1.3 %	Decomposition	Not available
Upper Explosive Limit	12.8 %	Vapor Pressure	66.3 mmHg
Vapor Density (air=1)	3.9	Specific Gravity (water=1)	Not available
Water Solubility	Negligible	Partition coefficient: n- octanol/water	Not available
Viscosity	450 cps	Solubility (Other)	Hydrocarbons
Density	0.9 (relative)	VOC	<250 g/L

Other Information

No additional information available.

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal conditions of use.

Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.



Material Name: CCW-702 LV

Incompatible Materials

Strong acids, strong oxidizing agents

Hazardous decomposition products

Oxides of carbon, hydrocarbons. Fumes may be irritating.

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness.

Skin Contact

Causes skin irritation.

Eye Contact

Causes serious eye irritation.

Ingestion

May be fatal if swallowed and enters airways. May cause gastrointestinal irritation.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Toluene (108-88-3)

Oral LD50 Rat >7000 mg/kg Dermal LD50 Rabbit 12 - 14 g/kg Inhalation LC50 Rat 30 - 35 mg/L

Acetone (67-64-1) Oral LD50 Rat 5800 mg/kg Dermal LD50 Guinea pig >7246 mg/kg Inhalation LC50 Rat 32000 ppm 4 h

Coumarone-indene resin (63393-89-5) Oral LD50 Rat >16000 mg/kg Phthalo blue (Mixture) Oral LD50 Rat 8532 mg/kg Dermal LD50 Rabbit >5 g/kg

tert-Butyl acetate (540-88-5) Oral LD50 4500 mg/kg Dermal LD50 >2000 mg/kg Inhalation LC50 Rat 12.52 mg/L 4 h

Immediate Effects

Harmful if inhaled. May be fatal if swallowed and enters airways. Cause skin irritation. Causes serious eye irritation. Causes damage to central nervous system. May cause respiratory irritation. May cause drowsiness or dizziness.



Material Name: CCW-702 LV

Delayed Effects

Causes damage to organs through prolonged or repeated exposure: central nervous system, blood.

Irritation/Corrosivity Data

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation.

Respiratory Sensitization No data available.

No data available.

Dermal Sensitization

No data available.

Component Carcinogenicity

Toluene		108-88-3
	ACGIH:	A4 - Not Classifiable as a Human Carcinogen
	IARC:	Monograph 71 [1999]; Monograph 47 [1989] (Group 3 (not classifiable))
Acetone		67-64-1
	ACGIH:	A4 - Not Classifiable as a Human Carcinogen

Germ Cell Mutagenicity

No data available.

Tumorigenic Data

No data available

Reproductive Toxicity

No data available.

Specific Target Organ Toxicity - Single Exposure central nervous system

Specific Target Organ Toxicity - Repeated Exposure blood, central nervous system

Aspiration hazard

May be fatal if swallowed and enters airways.

Medical Conditions Aggravated by Exposure

Aspiration into the lungs may cause chemical pneumonitis.

Additional Data

No additional information available.

Section 12 - ECOLOGICAL INFORMATION



Material Name: CCW-702 LV

Ecotoxicity

Avoid release to the environment.

Component Analysis - Aquatic Toxicity

Toluene	108-88-3				
Fish:	LC50 96 h Pimephales promelas 15.22 - 19.05 mg/L [flow-through] (1 day old); LC50 96 h Pimephales promelas 12.6 mg/L [static]; LC50 96 h Oncorhynchus mykiss 5.89 - 7.81 mg/L [flow-through]; LC50 96 h Oncorhynchus mykiss 14.1 - 17.16 mg/L [static]; LC50 96 h Oncorhynchus mykiss 5.8 mg/L [semi-static]; LC50 96 h Lepomis macrochirus 11 - 15 mg/L [static]; LC50 96 h Cryzias latipes 54 mg/L [static]; LC50 96 h Poecilia reticulata 28.2 mg/L [semi-static]; LC50 96 h Poecilia reticulata 50.87 - 70.34 mg/L [static]				
Algae:	EC50 96 h Pseudokirchneriella subcapitata >433 mg/L IUCLID; EC50 72 h Pseudokirchneriella subcapitata 12.5 mg/L [static] EPA				
Invertebrate:	EC50 48 h Daphnia magna 5.46 - 9.83 mg/L [static] EPA; EC50 48 h Daphnia magna 11.5 mg/L IUCLID				
Acetone	67-64-1				
Fish:	LC50 96 h Oncorhynchus mykiss 4.74 - 6.33 mL/L; LC50 96 h Pimephales promelas 6210 - 8120 mg/L [static]; LC50 96 h Lepomis macrochirus 8300 mg/L				
Invertebrate:	EC50 48 h Daphnia magna 10294 - 17704 mg/L [static] EPA; EC50 48 h Daphnia magna 12600 - 12700 mg/L IUCLID				
Phthalo blue	Mixture				
Fish:	LC50 96 h Pimephales promelas 161 mg/L [static]				
Invertebrate:	EC50 48 h Daphnia magna >500 mg/L IUCLID				
tert-Butyl acetate	540-88-5				
Fish:	LC50 96 h Pimephales promelas 296 - 362 mg/L [flow-through]; LC50 96 hr Oncorhynchus mykiss 240 mg/L				
Invertebrate:	EC50 48 hr Daphnia magna 350 mg/L				

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential



Material Name: CCW-702 LV

No information available for the product.

Mobility

No information available for the product.

Other Toxicity

No additional information available.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents/container in accordance with local/regional/national/international regulations.

Section 14 - TRANSPORT INFORMATION

US DOT Information: Shipping Name:Adhesives Hazard Class: 3 UN/NA #: UN1133 Packing Group: II Required Label(s): 3 Additional information: Special Provisions (172.102): 149, B52, IB2, T4, TP1, TP8

IATA Information: UN#: UN1133

IMDG Information: UN#: UN1133

TDG Information: UN#: UN1133

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Toluene	108-88-3
SARA 313:	1 % de minimis concentration
CERCLA:	1000 lb final RQ; 454 kg final RQ



Material Name: CCW-702 LV

Acetone67-64-1CERCLA:5000 lb final RQ; 2270 kg final RQtert-Butyl acetate540-88-5CERCLA:5000 lb final RQ; 2270 kg final RQ

SARA Section 311/312 (40 CFR 370 Subparts B and C) Acute Health: Yes Chronic Health: Yes Fire: Yes Pressure: No Reactivity: No

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Toluene	108-88-3	Yes	Yes	Yes	Yes	Yes
Acetone	67-64-1	Yes	Yes	Yes	Yes	Yes
tert-Butyl acetate	540-88-5	Yes	Yes	Yes	Yes	Yes

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects

Toluene	108-88-3
Repro/Dev. Tox	developmental toxicity, 1/1/1991

Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

Toluene	108-88-3
	1 %
Acetone	67-64-1
	1 %
tert-Butyl acetate	540-88-5
	1 %

Component Analysis - Inventory Toluene (108-88-3)

	KR - KR - KECI/KECL TCCA	CN	NZ	MX
--	-----------------------------	----	----	----

Product #: 316148



Material Name: CCW-702 LV

ai Name. GGW-702 LV Floudel										ICI #. 31	
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes
Aceto	ne (67-	-64-1)									

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Styrene/isoprene copolymer (25038-32-8)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	No

Coumarone-indene resin (63393-89-5)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	No

Phthalo blue (Mixture)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

C.I. Solvent Red 26 (4477-79-6)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

tert-Butyl acetate (540-88-5)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Product #: 316148



Material Name: CCW-702 LV

Section 16 - OTHER INFORMATION

HMIS Rating

Health: 2* Fire: 3 Reactivity: 0 Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

NFPA Ratings

Health: 2 Fire: 3 Reactivity: 0 Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes

New SDS: May 27, 2015

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP -Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG -Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU -European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts[™] - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit: US - United States.

Other Information

Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, CCWI Company must rely upon the hazard evaluation of such components submitted by that product's manufacturer or importer. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use