



**COLOR RELEASE - 20# PL GRAY/DARK GRAY**

Version 3.0  
REVISION DATE: 07/08/2012

Print Date 08/26/2013

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : COLOR RELEASE - 20# PL GRAY/DARK GRAY  
Product code : CCRE P020 355  
  
COMPANY : Increte Systems - A Division of The Euclid Chemical Company  
1611 Gunn Highway  
Odessa, FL 33556  
Telephone : 1-800-752-4626  
Emergency Phone: : U.S. only: 1-800-424-9300  
International Users Call Collect: 1-703-527-3887

**SECTION 2 - HAZARDS IDENTIFICATION**

**Emergency Overview**

Gray. Powder. May cause coughing and wheezing. Dust may irritate respiratory tract. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : May cause coughing and wheezing. Dust may irritate respiratory tract.  
Eyes : Dust may cause eye irritation. May cause mechanical irritation or abrasion. Direct contact may cause temporary redness and discomfort.  
Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.  
Skin : May cause mild irritation.

**Aggravated Medical Conditions**

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**


Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica.

**SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
Calcium stearate	1592-23-0	40.0 - 70.0
Calcium Carbonate (Limestone)	1317-65-3	40.0 - 70.0
Iron oxide	1317-61-9	10.0 - 30.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1.0

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

**COLOR RELEASE - 20# PL GRAY/DARK GRAY**

Version 3.0

Print Date 08/26/2013

REVISION DATE: 07/08/2012

- |              |   |                                                                                                                                           |
|--------------|---|-------------------------------------------------------------------------------------------------------------------------------------------|
| Inhalation   | : | Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.                                  |
| Eye contact  | : | Flush with water for 15 minutes. If irritation persists, get medical attention.                                                           |
| Skin contact | : | Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately. |
| Ingestion    | : | Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.                        |

**SECTION 5 - FIRE FIGHTING MEASURES**

- |                                       |   |                                                                                                                         |
|---------------------------------------|---|-------------------------------------------------------------------------------------------------------------------------|
| Flash point                           | : | Not available.                                                                                                          |
| Method                                | : | Not available.                                                                                                          |
| Lower explosion limit                 | : | Not available.                                                                                                          |
| Upper explosion limit                 | : | Not available.                                                                                                          |
| Autoignition temperature              | : | Not available.                                                                                                          |
| Extinguishing media                   | : | This product is not expected to burn under normal conditions of use. Use that which is appropriate to the surroundings. |
| Hazardous combustion products         | : | Not available.                                                                                                          |
| Protective equipment for firefighters | : | Not applicable. Product is not expected to burn.                                                                        |
| Fire and explosion conditions         | : | This product not expected to ignite under normal conditions of use.                                                     |

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**


Use appropriate protective equipment. Avoid contact with material. Dampen material with water to control dusting. Scoop up and transfer to appropriate container for disposal. Flush spill area with water.

**SECTION 7 - HANDLING AND STORAGE**

Store under normal warehouse conditions in sealed containers. Handle in compliance with common hygienic practices. Clean hands thoroughly after handling.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION****Personal protection equipment**

- |                        |   |                                                                                                                                                                                                                        |
|------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Respiratory protection | : | Wear appropriate, properly fitted NIOSH/MSHA approved dust respirator where airborne concentrations are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use. |
| Hand protection        | : | Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.                                                                                                                              |
| Eye protection         | : | Wear appropriate eye protection.                                                                                                                                                                                       |

**COLOR RELEASE - 20# PL GRAY/DARK GRAY**

Version 3.0

Print Date 08/26/2013

REVISION DATE: 07/08/2012

- Skin and body protection : Prevent contact with shoes and clothing. Use rubber apron and overshoes.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

**Exposure Limits**

<b>Chemical Name</b>	<b>CAS Number</b>	<b>Regulation</b>	<b>Limit</b>	<b>Form</b>
Calcium stearate	1592-23-0	ACGIH TWA:	10 mg/m <sup>3</sup>	
Calcium Carbonate (Limestone)	1317-65-3	OSHA PEL: OSHA PEL: ACGIH TWA: ACGIH TWA: OSHA TWA: OSHA TWA:	5 mg/m <sup>3</sup> 15 mg/m <sup>3</sup> 3 mg/m <sup>3</sup> 10 mg/m <sup>3</sup> 15 mg/m <sup>3</sup> 5 mg/m <sup>3</sup>	Respirable fraction. Total dust. Respirable particles. Inhalable particles. Total dust. Respirable fraction.
Iron oxide	1317-61-9	ACGIH TWA: ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA: OSHA TWA:	3 mg/m <sup>3</sup> 10 mg/m <sup>3</sup> 15 mg/m <sup>3</sup> 5 mg/m <sup>3</sup> 15 mg/m <sup>3</sup> 5 mg/m <sup>3</sup>	Respirable particles. Inhalable particles. Total dust. Respirable fraction. Total dust. Respirable fraction.
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL: ACGIH TWA:	0.1 mg/m <sup>3</sup> 0.3 mg/m <sup>3</sup> 15 mg/m <sup>3</sup> 5 mg/m <sup>3</sup> 0.025 mg/m <sup>3</sup>	Respirable. Total dust. Total dust. Respirable fraction. Respirable fraction.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

- Form : Powder
- Color : Gray
- Odor : None
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Not available.
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : Not available.
- Water solubility : Not available.
- Specific Gravity : 1.63



**COLOR RELEASE - 20# PL GRAY/DARK GRAY**

Version 3.0  
REVISION DATE: 07/08/2012

Print Date 08/26/2013

% Volatile Weight : 0.0 %

**SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid : Not Applicable.  
Stability : Material is stable under normal storage, handling, and use.  
Hazardous polymerization : Will not occur under normal conditions.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

No Data Available

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Waste not regulated under RCRA. Dispose of in compliance with state and local regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

**CFR / DOT:**

Not Regulated

**TDG:**

Not Regulated

**IMDG:**

Not Regulated

**SECTION 15 - REGULATORY INFORMATION**

**North American Inventories:**

All components are listed or exempt from the TSCA inventory.  
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**



**COLOR RELEASE - 20# PL GRAY/DARK GRAY**

Version 3.0

Print Date 08/26/2013

REVISION DATE: 07/08/2012

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard  
Chronic Health Hazard

OSHA Hazardous Components :

Calcium stearate 1592-23-0  
Calcium Carbonate (Limestone) 1317-65-3  
Iron oxide 1317-61-9  
Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

OSHA Status: Considered : Irritant  
hazardous based on the Carcinogen  
following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and : 0 g/l  
exempt solvent)  
VOC Method 310 : 0 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

**U.S. State Regulations:**

MASS RTK Components : Calcium Carbonate (Limestone) 1317-65-3  
Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

Penn RTK Components : Calcium stearate 1592-23-0  
Calcium Carbonate (Limestone) 1317-65-3  
Iron oxide 1317-61-9

NJ RTK Components : Calcium stearate 1592-23-0  
Calcium Carbonate (Limestone) 1317-65-3  
Iron oxide 1317-61-9  
Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

Components under California Proposition 65:


WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	1
Flammability	0
Reactivity	0
PPE	

0 = Minimum  
1 = Slight  
2 = Moderate  
3 = Serious  
4 = Severe



**COLOR RELEASE - 20# PL GRAY/DARK GRAY**

Version 3.0

Print Date 08/26/2013

REVISION DATE: 07/08/2012

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

**Legend**

ACGIH - American Conference of Governmental Hygienists

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

DOT - Department of Transportation

DSL - Domestic Substance List

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information System