

Version: 1.0 Revision Date: 07/29/2015

SAFETY DATA SHEET

1. Identification

Material name: EUCO ROCK Material: 035A 50

Recommended use and restriction on use

Recommended use: Cement, Portland, chemicals **Restrictions on use:** Not known.

Manufacturer/Importer/Supplier/Distributor Information

EUCLID CHEMICAL COMPANY 19218 REDWOOD ROAD CLEVELAND OH 44110 US

Contact person: Telephone: Emergency telephone number:

EH&S Department 216-531-9222 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 1
Skin sensitizer	Category 1B
Carcinogenicity	Category 1A
Specific Target Organ Toxicity - Single Exposure	Category 3

Unknown toxicity - Health

Acute toxicity, oral		79.88 %
Acute toxicity, derr	nal	86.89 %
Acute toxicity, inha	lation, vapor	100 %
Acute toxicity, inha	alation, dust or mist	100 %
Acute toxicity, inha	lation, vapor	100 %

Unknown toxicity - Environment Acute hazards to the aquatic

Acute hazards to the aquatic	98.2 %
environment	
Chronic hazards to the aquatic	100 %
environment	

Label Elements

Hazard Symbol:





Signal Word:	Danger
Hazard Statement:	Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause cancer. May cause respiratory irritation.
Precautionary Statement:	
Prevention:	Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Use only outdoors or in a well-ventilated area.
Response:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Immediately call a POISON CENTER/doctor. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up. Store in well-ventilated place. Keep container tightly closed.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	40 - 70%
Portland cement	65997-15-1	15 - 40%
Calcium oxide	1305-78-8	7 - 13%
Aluminum oxide	1344-28-1	5 - 10%
Calcium Salt	26499-65-0	3 - 7%
Amorphous silica	7631-86-9	1 - 5%

Fumed silica	69012-64-2	1 - 5%
Calcium salt	7778-18-9	1 - 5%
Sulphur trioxide	7446-11-9	1 - 5%
Magnesium oxide	1309-48-4	0.5 - 1.5%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures		
Ingestion:	Call a POISON CENTER/doctor//if you feel unwell. Rinse mouth.	
Inhalation:	Move to fresh air.	
Skin Contact:	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.	
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Call a physician or poison control center immediately.	
Most important symptoms/effect	s, acute and delayed	
Symptoms:	Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping. Extreme irritation of eyes and mucous membranes, including burning and tearing. Respiratory tract irritation.	
Indication of immediate medical a	ttention and special treatment needed	
Treatment:	Symptoms may be delayed.	
5. Fire-fighting measures		
General Fire Hazards:	No unusual fire or explosion hazards noted.	
Suitable (and unsuitable) e	xtinguishing media	
Suitable (and unsuitable) e Suitable extinguishing media:	xtinguishing media Use fire-extinguishing media appropriate for surrounding materials.	
Suitable extinguishing		
Suitable extinguishing media: Unsuitable extinguishing	Use fire-extinguishing media appropriate for surrounding materials.	
Suitable extinguishing media: Unsuitable extinguishing media: Specific hazards arising from	Use fire-extinguishing media appropriate for surrounding materials. Do not use water jet as an extinguisher, as this will spread the fire. During fire, gases hazardous to health may be formed.	
Suitable extinguishing media: Unsuitable extinguishing media: Specific hazards arising from the chemical:	Use fire-extinguishing media appropriate for surrounding materials. Do not use water jet as an extinguisher, as this will spread the fire. During fire, gases hazardous to health may be formed.	



6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.
Methods and material for containment and cleaning up:	Collect spillage in containers, seal securely and deliver for disposal according to local regulations.
Notification Procedures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.
7. Handling and storage	
7. Handling and storage Precautions for safe handling:	Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not get in eyes. Wash hands thoroughly after handling. Avoid contact with skin. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	US. ACGIH Threshold Limit Values (2011)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Crystalline Silica (Quartz)/ Silica Sand - Total dust.	TWA	0.3 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Portland cement - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Portland cement - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Portland cement -	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air



Respirable fraction.			Contaminants (29 CFR 1910.1000) (02 2006)
Portland cement	TWA	50 millions of particles per cubic	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
		foot of air	
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Aluminum oxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Salt - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Calcium Salt - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Salt - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Amorphous silica	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Fumed silica	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium salt - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Calcium salt - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium salt - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Magnesium oxide - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Magnesium oxide - Total particulate.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)



Г

Т

Chemical name	type	Exposure Limit Values	Source
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWAEV	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Portland cement - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Portland cement - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Portland cement	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Portland cement - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Portland cement - Respirable dust.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Aluminum oxide - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Aluminum oxide - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical



			Agents) (11 2010)
Aluminum oxide - Total dust as Al	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Salt - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Salt - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Salt - Inhalable fraction.	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)



Calcium Salt - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Salt - Respirable dust.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Amorphous silica - Total	TWA	4 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable.	TWA	1.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Amorphous silica - Respirable dust.	TWA	6 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Fumed silica - Total fume.	TWA	4 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Fumed silica - Respirable fume.	TWA	1.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Fumed silica - Respirable.	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Fumed silica - Respirable dust and/or fume.	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium salt - Inhalable	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium salt - Inhalable fraction.	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium salt - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)



	Calcium salt - Respirable dust.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	Sulphur trioxide - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Ċ	opriate Engineering ontrols	Observ limits a		
man		5, 5001 05	personal protective equipi	
	General information:	ventilat rates s enclosi mainta	Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.	
	Eye/face protection:		a full-face respirator, if neede gles) and a face shield.	d. Wear safety glasses with side shields
	Skin Protection Hand Protection:	Use si	uitable protective gloves if ris	k of skin contact.

or manufacturer for specific information.

local supervisor.

Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional

contaminated clothing before reuse. Avoid contact with skin.

In case of inadequate ventilation use suitable respirator. Seek advice from

Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Do not get in eyes. Wash

9. Physical and chemical properties

Other:

Respiratory Protection:

Hygiene measures:

Appearance

Physical state:	solid
Form:	Powder
Color:	Gray
Odor:	Odorless
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.

Version: 1.0 Revision Date: 07/29/2015



	Ne dete evelleble
Evaporation rate:	No data available.
Flammability (solid, gas):	No
Upper/lower limit on flammability or explos	ive limits
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	No data available.
Relative density:	3.0
Solubility(ies)	
Solubility in water:	Miscible with water.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of Hazardous Reactions:	No data available.
Conditions to Avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of ex Ingestion:	Aposure May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	Causes skin irritation.
Eye contact:	Causes serious eye damage.



Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral Product:	No data available.
Dermal Product:	No data available.
Inhalation Product:	No data available.
Specified substance(s): Calcium oxide	LC 50 (Rat, 4 h): 160 mg/m3
Aluminum oxide	NOAEL (Rat, 4 h): 10 mg/m3
Amorphous silica	LC 50 (Rat, 4 h): > 58.8 mg/l
Fumed silica	LC 50 (Rat, 4 h): > 2.08 mg/l
Calcium salt	LC 50 (Rat, 4 h): > 3.26 mg/l
Sulphur trioxide	LC 0): 0.461 mg/l LC 0): 0.699 mg/l LC 100): 1.47 mg/l LC 100): 0.087 mg/l LC 100): 0.699 mg/l LC 40): 0.699 mg/l LC 0): 0.718 mg/l LC 50): 1.61 mg/l
Repeated dose toxicity Product:	No data available.
Skin Corrosion/Irritation Product:	No data available.
Serious Eye Damage/Eye Irritati Product:	on No data available.



Specified substance(s):

Calcium oxide	in vivo (Rabbit, 24 hrs): Category 1
Aluminum oxide	in vivo (Rabbit, 24 hrs): Not irritating
Amorphous silica	in vivo (Rabbit, 24 hrs): Not irritating
Calcium salt	in vivo (Rabbit, 72 hrs): Not irritating
Sulphur trioxide	Highly irritating
Magnesium oxide	Slightly irritating

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity Product:

No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Crystalline Silica	Overall evaluation: Carcinogenic to humans.
(Quartz)/ Silica	
Sand	

Sulphur trioxide Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Crystalline Silica Known To Be Human Carcinogen. (Quartz)/ Silica Sand Sulphur trioxide Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): No carcinogenic components identified

Germ Cell Mutagenicity

In vitro Product:

No data available.

In vivo Product:

No data available.

Reproductive toxicity Product:

No data available.

```
Specific Target Organ Toxicity - Single Exposure
Product: No data available.
```



Specific Target Organ To Product:	xicity - Repeated Exposure No data available.	
Aspiration Hazard Product:	No data available.	
Other effects:	No data available.	
12. Ecological information	on	

Ecotoxicity:

Acute hazards to the aquatic environment:		
Fish Product:	No data available.	
Specified substance(s): Calcium salt	LC 50 (Fathead minnow (Pimephales promelas), 96 h): > 1,970 mg/l Mortality	
Aquatic Invertebrates Product:	No data available.	
Specified substance(s): Calcium salt	LC 50 (Water flea (Daphnia magna), 24 h): > 1,970 mg/l Mortality LC 50 (Water flea (Ceriodaphnia dubia), 24 h): > 1,940 mg/l Mortality LC 50 (Water flea (Ceriodaphnia dubia), 48 h): > 1,970 mg/l Mortality LC 50 (Water flea (Ceriodaphnia dubia), 48 h): > 1,910 mg/l Mortality	

Chronic hazards to the aquatic environment:

Fish Product:	No data available.
Specified substance(s): Calcium oxide	NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted
Aluminum oxide	NOAEL (Pimephales promelas, 28 d): 4.7 mg/l experimental result
Sulphur trioxide	NOAEL (Jordanella floridae, 65 d): 0.025 mg/l interpreted
Aquatic Invertebrates Product:	No data available.
Toxicity to Aquatic Plants Product:	No data available.
Persistence and Degradability	

Biodegradation



Product:	No data available.
BOD/COD Ratio Product:	No data available.
Bioaccumulative Potential Bioconcentration Factor (BC Product:	F) No data available.
Partition Coefficient n-octan Product:	ol / water (log Kow) No data available.
Mobility in Soil:	No data available.
Other Adverse Effects:	No data available.
13. Disposal considerations	
Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.
14. Transport information	
TDG:	
Not Regulated	
CFR / DOT:	
Not Regulated	
IMDG:	
Not Regulated	
15. Regulatory information	

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) None present or none present in regulated quantities.



US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical Identity Formaldehyde

OSHA hazard(s)

Acute toxicity Skin irritation Skin sensitization Flammability respiratory tract irritation Respiratory sensitization Cancer Eye irritation

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity	
Sulphur trioxide	1000 lbs.	
Formaldehyde	100 lbs.	

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

	<u>Reportable</u>	
Chemical Identity	<u>quantity</u>	Threshold Planning Quantity
Sulphur trioxide	100 lbs.	100 lbs.
Formaldehyde	100 lbs.	500 lbs.

SARA 304 Emergency Release Notification

Chemical Identity	<u>Reportable quantity</u>
Sulphur trioxide	1000 lbs.
Formaldehyde	100 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Sulphur trioxide	100lbs
Formaldehyde	500lbs
Crystalline Silica (Quartz)/	500 lbs
Silica Sand	
Portland cement	500 lbs
Calcium oxide	500 lbs
Aluminum oxide	500 lbs
Calcium Salt	500 lbs
Amorphous silica	500 lbs
Fumed silica	500 lbs
Calcium salt	500 lbs
Magnesium oxide	500 lbs

SARA 313 (TRI Reporting)

Chemical Identity

Aluminum oxide

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3) None present or none present in regulated quantities.



Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Chemical Identity		
Sulphur trioxide		
Formaldehyde		

Reportable quantity 10000 lbs 15000 lbs

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Crystalline Silica (Quartz)/ Silica Sand Portland cement Calcium oxide Aluminum oxide Calcium Salt Amorphous silica Fumed silica Calcium salt Sulphur trioxide

US. Massachusetts RTK - Substance List

Chemical Identity

Crystalline Silica (Quartz)/ Silica Sand Portland cement Calcium oxide Aluminum oxide Calcium Salt Amorphous silica Fumed silica Calcium salt Sulphur trioxide Formaldehyde

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Crystalline Silica (Quartz)/ Silica Sand Portland cement Calcium oxide Aluminum oxide Calcium Salt Amorphous silica Fumed silica Calcium salt Sulphur trioxide

US. Rhode Island RTK

Chemical Identity

Aluminum oxide Sulphur trioxide

Other Regulations:



Regulatory VOC (less water and exempt solvent):	0 g/l		
VOC Method 310:	0.00 %		
Inventory Status: Australia AICS:		One or more components in this product are not listed on or exempt from the Inventory.	
Canada DSL Inventory List:		One or more components in this product are not listed on or exempt from the Inventory.	
EINECS, ELINCS or NLP:		One or more components in this product are not listed on or exempt from the Inventory.	
Japan (ENCS) List:		One or more components in this product are not listed on or exempt from the Inventory.	
China Inv. Existing Chemical Substances:		One or more components in this product are not listed on or exempt from the Inventory.	
Korea Existing Chemicals Inv. (KECI):		One or more components in this product are not listed on or exempt from the Inventory.	
Canada NDSL Inventory:		One or more components in this product are not listed on or exempt from the Inventory.	
Philippines PICCS:		One or more components in this product are not listed on or exempt from the Inventory.	
US TSCA Inventory:		One or more components in this product are not listed on or exempt from the Inventory.	
New Zealand Inventory of Chemicals:		All components in this product are listed on or exempt from the Inventory.	
Japan ISHL Listing:		One or more components in this product are not listed on or exempt from the Inventory.	
Japan Pharmacopoeia Listing:		One or more components in this product are not listed on or exempt from the Inventory.	

16.Other information, including date of preparation or last revision

Revision Date:	07/29/2015
Version #:	1.0



Further Information:

Disclaimer:

No data available.

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.