

# Safety Data Sheet

## MasterSeal HLM 5000RG also HLM 5000 ROLLER GRADE

Revision date : 2015/07/02

Page: 1/12

Version: 2.0

(30605604/SDS\_GEN\_US/EN)

### 1. Identification

**Product identifier used on the label**

## MasterSeal HLM 5000RG also HLM 5000 ROLLER GRADE

**Recommended use of the chemical and restriction on use**

Recommended use\*: for industrial and professional users

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

**Details of the supplier of the safety data sheet**

Company:

BASF CORPORATION  
100 Park Avenue  
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

**Emergency telephone number**

CHEMTREC: 1-800-424-9300  
BASF HOTLINE: 1-800-832-HELP (4357)

**Other means of identification**

Chemical family: No data available.

---

### 2. Hazards Identification

**According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200**

**Classification of the product**

Asp. Tox.	1	Aspiration hazard
Flam. Liq.	3	Flammable liquids
Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	1	Serious eye damage/eye irritation
Muta.	1B	Germ cell mutagenicity
Carc.	1B	Carcinogenicity
Repr.	1B (fertility)	Reproductive toxicity

# Safety Data Sheet

## MasterSeal HLM 5000RG also HLM 5000 ROLLER GRADE

Revision date : 2015/07/02

Page: 2/12

Version: 2.0

(30605604/SDS\_GEN\_US/EN)

Repr. 1B (unborn child) Reproductive toxicity

### Label elements

Pictogram:



Signal Word:

Danger

Hazard Statement:

H226 Flammable liquid and vapour.  
H318 Causes serious eye damage.  
H315 Causes skin irritation.  
H304 May be fatal if swallowed and enters airways.  
H350 May cause cancer.  
H340 May cause genetic defects.  
H360 May damage fertility. May damage the unborn child.

Precautionary Statements (Prevention):

P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P202 Do not handle until all safety precautions have been read and understood.  
P243 Take precautionary measures against static discharge.  
P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
P264 Wash with plenty of water and soap thoroughly after handling.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P242 Use only non-sparking tools.

Precautionary Statements (Response):

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER or doctor/physician.  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.  
P332 + P313 If skin irritation occurs: Get medical advice/attention.  
P331 Do NOT induce vomiting.  
P362 + P364 Take off contaminated clothing and wash before reuse.  
P370 + P378 In case of fire: Use... to extinguish.

Precautionary Statements (Storage):

P405 Store locked up.  
P403 + P235 Store in a well-ventilated place. Keep cool.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection point.

# Safety Data Sheet

## MasterSeal HLM 5000RG also HLM 5000 ROLLER GRADE

Revision date : 2015/07/02

Page: 3/12

Version: 2.0

(30605604/SDS\_GEN\_US/EN)

### Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

### 3. Composition / Information on Ingredients

#### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
14807-96-6	>= 25.0 - < 50.0%	talc
1305-78-8	>= 7.0 - < 10.0%	calcium oxide
8052-41-3	>= 5.0 - < 15.0%	Stoddard solvent
64742-95-6	>= 3.0 - < 5.0%	solvent naphtha
64742-52-5	>= 3.0 - < 5.0%	Distillates (petroleum), hydrotreated heavy naphthenic
95-63-6	>= 1.0 - < 3.0%	1,2,4-trimethylbenzene
64742-53-6	>= 0.3 - < 3.0%	Distillates (petroleum), hydrotreated light naphthenic
77-58-7	>= 0.2 - < 0.3%	dibutyltin dilaurate

#### According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
77-58-7	>= 0.2 - < 0.3%	dibutyltin dilaurate
95-63-6	>= 1.0 - < 3.0%	1,2,4-trimethylbenzene
1305-78-8	>= 7.0 - < 10.0%	calcium oxide
8052-41-3	>= 5.0 - < 15.0%	Stoddard solvent
64742-95-6	>= 3.0 - < 5.0%	solvent naphtha

### 4. First-Aid Measures

#### Description of first aid measures

##### General advice:

First aid personnel should pay attention to their own safety. Remove contaminated clothing.

##### If inhaled:

Remove the affected individual into fresh air and keep the person calm. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

##### If on skin:

Wash thoroughly with soap and water. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

##### If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

##### If swallowed:

Rinse mouth and then drink plenty of water. Do not induce vomiting due to aspiration hazard. Do not induce vomiting unless told to by a poison control center or doctor.

#### Most important symptoms and effects, both acute and delayed

# Safety Data Sheet

## MasterSeal HLM 5000RG also HLM 5000 ROLLER GRADE

Revision date : 2015/07/02

Page: 4/12

Version: 2.0

(30605604/SDS\_GEN\_US/EN)

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Hazards: No applicable information available.

### Indication of any immediate medical attention and special treatment needed

#### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

## 5. Fire-Fighting Measures

### Extinguishing media

Suitable extinguishing media:  
dry powder, alcohol-resistant foam

Unsuitable extinguishing media for safety reasons:  
water jet

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:  
carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

### Advice for fire-fighters

Protective equipment for fire-fighting:  
Wear a self-contained breathing apparatus.

### Further information:

The degree of risk is governed by the burning substance and the fire conditions. Containers may rocket or explode in heat of fire. Keep containers cool by spraying with water if exposed to fire. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.

---

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Avoid prolonged inhalation. Avoid contact with the skin, eyes and clothing. Avoid all sources of ignition: heat, sparks, open flame.

### Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers). Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

### Methods and material for containment and cleaning up

For large amounts: Pump off product.

For residues: Pick up with inert absorbent material (e.g. sand, earth etc.). Correctly dispose of recovered product immediately.

---

# Safety Data Sheet

## MasterSeal HLM 5000RG also HLM 5000 ROLLER GRADE

Revision date : 2015/07/02

Page: 5/12

Version: 2.0

(30605604/SDS\_GEN\_US/EN)

### 7. Handling and Storage

#### Precautions for safe handling

Take precautionary measures against static discharges. Keep away from sources of ignition - No smoking. Provide good room ventilation even at ground level (vapours are heavier than air).

Protection against fire and explosion:

Sources of ignition should be kept well clear. Take precautionary measures against static discharges. Substance/product can form explosive mixture with air. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

#### Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container tightly closed and in a well-ventilated place. Keep away from heat. Avoid all sources of ignition: heat, sparks, open flame.

### 8. Exposure Controls/Personal Protection

#### Components with occupational exposure limits

dibutyltin dilaurate	OSHA PEL	PEL 0.1 mg/m <sup>3</sup> (tin (Sn)); TWA value 0.1 mg/m <sup>3</sup> (tin (Sn)); SKIN_FINAL (tin (Sn)); The substance can be absorbed through the skin.
	ACGIH TLV	TWA value 0.1 mg/m <sup>3</sup> (tin (Sn)); STEL value 0.2 mg/m <sup>3</sup> (tin (Sn)); Skin Designation (tin (Sn)); The substance can be absorbed through the skin.
1,2,4-trimethylbenzene	OSHA PEL	TWA value 25 ppm 125 mg/m <sup>3</sup> ;
	ACGIH TLV	TWA value 25 ppm ;
calcium oxide	OSHA PEL	PEL 5 mg/m <sup>3</sup> ; TWA value 5 mg/m <sup>3</sup> ;
	ACGIH TLV	TWA value 2 mg/m <sup>3</sup> ;
Stoddard solvent	OSHA PEL	PEL 500 ppm 2,900 mg/m <sup>3</sup> ;
	ACGIH TLV	TWA value 100 ppm ;

# Safety Data Sheet

## MasterSeal HLM 5000RG also HLM 5000 ROLLER GRADE

Revision date : 2015/07/02

Page: 6/12

Version: 2.0

(30605604/SDS\_GEN\_US/EN)

talc	OSHA PEL	TWA value 20 millions of particles per cubic foot of air ; TWA value 2.4 millions of particles per cubic foot of air Respirable ; The exposure limit is calculated from the equation, $250/(\%SiO_2+5)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits. TWA value 0.1 mg/m <sup>3</sup> Respirable ; The exposure limit is calculated from the equation, $10/(\%SiO_2+2)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits. TWA value 0.3 mg/m <sup>3</sup> Total dust ; The exposure limit is calculated from the equation, $30/(\%SiO_2+2)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits. TWA value 2 mg/m <sup>3</sup> Respirable dust ; TWA value 0.3 mg/m <sup>3</sup> Total dust ; The exposure limit is calculated from the equation, $30/(\%SiO_2+2)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits. TWA value 0.1 mg/m <sup>3</sup> Respirable ; The exposure limit is calculated from the equation, $10/(\%SiO_2+2)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits. TWA value 2.4 millions of particles per cubic foot of air Respirable ; The exposure limit is calculated from the equation, $250/(\%SiO_2+5)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits.
	ACGIH TLV	TWA value 20 millions of particles per cubic foot of air ; TWA value 2 mg/m <sup>3</sup> Respirable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.
Distillates (petroleum), hydrotreated heavy naphthenic	OSHA PEL	PEL 5 mg/m <sup>3</sup> Mist ; PEL 500 ppm 2,000 mg/m <sup>3</sup> ; TWA value 5 mg/m <sup>3</sup> Mist ;
Distillates (petroleum), hydrotreated light naphthenic	OSHA PEL	PEL 5 mg/m <sup>3</sup> Mist ; PEL 500 ppm 2,000 mg/m <sup>3</sup> ; TWA value 5 mg/m <sup>3</sup> Mist ;
	ACGIH TLV	; Exposure by all routes should be carefully controlled to levels as low as possible. ; Included in the regulation, but with no data values - See the regulation for further details

### Advice on system design:

No applicable information available.

# Safety Data Sheet

## MasterSeal HLM 5000RG also HLM 5000 ROLLER GRADE

Revision date : 2015/07/02

Version: 2.0

Page: 7/12

(30605604/SDS\_GEN\_US/EN)

### Personal protective equipment

#### **Respiratory protection:**

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

#### **Hand protection:**

Wear chemical resistant protective gloves.

#### **Eye protection:**

Safety glasses with side-shields.

#### **Body protection:**

Body protection must be chosen based on level of activity and exposure., Antistatic apron

#### **General safety and hygiene measures:**

Avoid inhalation of dusts/mists/vapours. Avoid contact with the skin, eyes and clothing. Avoid prolonged and/or repeated contact with the skin. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

---

## 9. Physical and Chemical Properties

Form:	slightly viscous
Odour:	aromatic
Odour threshold:	No applicable information available.
Colour:	black
pH value:	not applicable
Freezing point:	No data available.
boiling temperature:	approx. 153.33 - 371.11 °C
Sublimation temperature:	No applicable information available.
Flash point:	123 °F
Flammability:	Flammable.
Lower explosion limit:	0.9 %(V)
Upper explosion limit:	7.0 %(V)
Vapour pressure:	approx. 8 mmHg ( 25 °C)
Density:	approx. 10.3 lb/USg ( 70 °F) approx. 1.23 g/cm3 ( 22 °C)
Relative density:	No applicable information available.
Bulk density:	900 - 1,600 kg/m3
Vapour density:	Heavier than air.
Thermal decomposition:	Vapours may form explosive mixture with air. No decomposition if stored and handled as prescribed/indicated.
Viscosity, dynamic:	No applicable information available.
Viscosity, kinematic:	No applicable information available.
Solubility in water:	( 20 °C) slightly soluble
Miscibility with water:	( 20 °C) not soluble
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.

# Safety Data Sheet

## MasterSeal HLM 5000RG also HLM 5000 ROLLER GRADE

Revision date : 2015/07/02

Page: 8/12

Version: 2.0

(30605604/SDS\_GEN\_US/EN)

Evaporation rate: No applicable information available.  
Other Information: If necessary, information on other physical and chemical parameters is indicated in this section.

---

### 10. Stability and Reactivity

#### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

#### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

#### Possibility of hazardous reactions

No hazardous reactions if stored and handled as prescribed/indicated.

#### Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame.

#### Incompatible materials

strong oxidizing agents

#### Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

Vapours may form explosive mixture with air. No decomposition if stored and handled as prescribed/indicated.

---

### 11. Toxicological information

#### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### Acute Toxicity/Effects

##### Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single skin contact. Aspiration of petroleum distillates may cause chemical pneumonitis

##### Oral

No applicable information available.

##### Inhalation

No applicable information available.

##### Dermal

No applicable information available.

##### Assessment other acute effects

No applicable information available.



# Safety Data Sheet

## MasterSeal HLM 5000RG also HLM 5000 ROLLER GRADE

Revision date : 2015/07/02

Page: 9/12

Version: 2.0

(30605604/SDS\_GEN\_US/EN)

### Irritation / corrosion

Assessment of irritating effects: Causes serious eye damage. May cause slight irritation to the skin. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

### Sensitization

Assessment of sensitization: Based on available Data, the classification criteria are not met.

### Aspiration Hazard

May also damage the lung at swallowing (aspiration hazard).

## Chronic Toxicity/Effects

### Repeated dose toxicity

Assessment of repeated dose toxicity: No reliable data was available concerning repeated dose toxicity.

### Genetic toxicity

Assessment of mutagenicity: Capable of causing genetic defects. The product has not been tested. The statement has been derived from the properties of the individual components.

### Carcinogenicity

Assessment of carcinogenicity: The substance caused cancer in animal studies. The product has not been tested. The statement has been derived from the properties of the individual components.

### Reproductive toxicity

Assessment of reproduction toxicity: Based on the ingredients, there is a suspicion of a toxic effect on reproduction.

### Teratogenicity

Assessment of teratogenicity: The potential to cause toxicity to development cannot be excluded when given in high doses.

## Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

---

## 12. Ecological Information

### Toxicity

#### Aquatic toxicity

Assessment of aquatic toxicity:

Acutely harmful for aquatic organisms. May cause long-term adverse effects in the aquatic environment. The product has not been tested. The statement has been derived from the properties of the individual components.

### Persistence and degradability

#### Assessment biodegradation and elimination (H<sub>2</sub>O)

Poorly biodegradable. The product has not been tested. The statement has been derived from the properties of the individual components.

### Mobility in soil

# Safety Data Sheet

## MasterSeal HLM 5000RG also HLM 5000 ROLLER GRADE

Revision date : 2015/07/02

Page: 10/12

Version: 2.0

(30605604/SDS\_GEN\_US/EN)

### Assessment transport between environmental compartments

The substance will not evaporate into the atmosphere from the water surface.

Adsorption to solid soil phase is expected.

---

## 13. Disposal considerations

### **Waste disposal of substance:**

Observe national and local legal requirements. Residues should be disposed of in the same manner as the substance/product.

---

## 14. Transport Information

### **Land transport**

USDOT

Hazard class:	C
Packing group:	III
ID number:	UN 1263
Hazard label:	CBL
Proper shipping name:	PAINT, COMBUSTIBLE LIQUID (contains SOLVENT NAPHTHA) Classified as combustible liquid in containers greater than 119 gallons.

### **Sea transport**

IMDG

Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3
Marine pollutant:	NO
Proper shipping name:	PAINT

### **Air transport**

IATA/ICAO

Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3
Proper shipping name:	PAINT

---

## 15. Regulatory Information

### Federal Regulations

#### **Registration status:**

Chemical TSCA, US released / listed

**EPCRA 311/312 (Hazard categories):** Acute; Chronic; Fire

#### **EPCRA 313:**

##### CAS Number

95-63-6

##### Chemical name

1,2,4-trimethylbenzene

# Safety Data Sheet

## MasterSeal HLM 5000RG also HLM 5000 ROLLER GRADE

Revision date : 2015/07/02

Page: 11/12

Version: 2.0

(30605604/SDS\_GEN\_US/EN)

### State regulations

#### State RTK

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
PA	8052-41-3	Stoddard solvent
	98-82-8	cumene
	14807-96-6	talc
	1305-78-8	calcium oxide
	95-63-6	1,2,4-trimethylbenzene
MA	64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic
	8052-41-3	Stoddard solvent
	98-82-8	cumene
	14807-96-6	talc
	1305-78-8	calcium oxide
NJ	95-63-6	1,2,4-trimethylbenzene
	64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic
	8052-41-3	Stoddard solvent
	14807-96-6	talc
	1305-78-8	calcium oxide
	95-63-6	1,2,4-trimethylbenzene
	64742-93-4	Asphalt, oxidized
98-82-8	cumene	
64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	

#### **CA Prop. 65:**

WARNING: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

#### **HMIS III rating**

Health: 2<sup>+</sup> Flammability: 2 Physical hazard: 0

---

## 16. Other Information

#### **SDS Prepared by:**

BASF NA Product Regulations

SDS Prepared on: 2015/07/02

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE

# Safety Data Sheet

## MasterSeal HLM 5000RG also HLM 5000 ROLLER GRADE

Revision date : 2015/07/02

Page: 12/12

Version: 2.0

(30605604/SDS\_GEN\_US/EN)

SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.  
END OF DATA SHEET