

Poly-AmericaCONSTRUCTION SHEETING

Poly-America's construction sheeting is made from polyethylene which provides for the optimum in economy and performance. Because of its good weatherability, chemical inertness and toughness, Poly-America's polyethylene sheeting has successfully been used for over 30 years in a wide variety of applications. Thickness ranges from as little as 0.3 mil (8 μ m) for paint drop cloths to 100 mil (2.5 mm) for use as landfill liners. Widths range up to 40 ft (12 m). If you have a special application or need more information on our products, contact your area sales representative.

Poly-America's standard sheeting will meet or exceed the following standard technical specifications:

CONSTRUCTION SHEETING

Commercial Item Description A-A-3174 Plastic Sheet, Polyolefin

Type 1 Class 1 Grade A or B Finish 1

ASTM C171 Standard Specification for Sheet Materials Used for Curing Concrete

ASTM D2103 Specification for Polyethylene Film and Sheeting

Standard Classification 12230

Note: If requested, custom sheeting can be made to meet the following

classifications:

12130 13130 13230 12330 13330

ASTM D4635 Standard Specification for Polyethylene Films Made from Low-Density Polyethylene for General Use and Packaging Applications

> Type 1 Class 2 Surface 2 Finish 1

ASTM D4397 Standard Specification for Polyethylene Sheeting for Construction, Industrial, and Agricultural Applications (see Table 1 for Impact Resistance and WVTR requirements)

TABLE 1

| Thickness | Dart Impact | WVTR | WVTR | WVTR |
|-----------|-------------|-----------------|----------|--------------|
| | ASTM D1709 | ASTM E96 | ASTM E96 | ASTM E96 |
| mils (µm) | g | g/100 sq in-day | perms | metric perms |
| 1(25) | 40 | 1.4 | .76 | .50 |
| 2(51) | 85 | .7 | .38 | .25 |
| 3(76) | 125 | .47 | .25 | .17 |
| 4(102) | 165 | .35 | .19 | .12 |
| 5(127) | 205 | .28 | .15 | .10 |
| 6(152) | 260 | .23 | .13 | .084 |
| 7(178) | 315 | .2 | .11 | .070 |
| 8(203) | 370 | .18 | .096 | .063 |
| 9(229) | 420 | .16 | .082 | .054 |
| 10(254) | 475 | .14 | .076 | .050 |

NOTE: The above is for our standard sheeting products. Poly-America will produce custom sheeting products to meet other classifications or specifications. Contact Poly-America to see how we can help you with your needs.