

**SUPER DIAMOND CLEAR VOX LOW VOC**

Version 2.0

Print Date 04/24/2013

REVISION DATE: 02/08/2013

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : SUPER DIAMOND CLEAR VOX LOW VOC
 Product code : 359ZZ-05

COMPANY : Euclid Chemical Company
 19218 Redwood Road
 Cleveland, OH 44110

Telephone : 1-800-321-7628
 Emergency Phone: : U.S. only: 1-800-424-9300
 International Users Call Collect: 1-703-527-3887

Product use : Coating

SECTION 2 - HAZARDS IDENTIFICATION**Emergency Overview**

White. Liquid. No serious effects anticipated under normal conditions of use. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : No serious effects anticipated under normal conditions of use.
 Eyes : Direct contact may cause mild irritation.
 Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.
 Skin : May cause mild irritation.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Repeated overexposure to Ethylene Glycol Butyl Ether may cause hemolysis of the red blood cells leading to possible liver and kidney damage. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Water	7732-18-5	> 60.0
Styrene-Acrylic Polymer	NJ TSRN# 51721300-6336P	15.0 - 40.0
Glycol ether solvent	112-34-5	1.0 - 5.0
Dipropylene glycol dibenzoate	27138-31-4	1.0 - 5.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**SUPER DIAMOND CLEAR VOX LOW VOC**

Version 2.0

Print Date 04/24/2013

REVISION DATE: 02/08/2013

Eye contact	:	Flush with water for 15 minutes. If irritation persists, get medical attention.
Skin contact	:	Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
Ingestion	:	Get medical attention. Do not induce vomiting.
Notes to physician	:	Not applicable.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point	:	Not available.
Method	:	Not applicable.
Lower explosion limit	:	Not available.
Upper explosion limit	:	Not available.
Autoignition temperature	:	Not available.
Extinguishing media	:	This product is not expected to burn under normal conditions of use.
Hazardous combustion products	:	Carbon monoxide and carbon dioxide can form. Smoke, fumes.
Protective equipment for firefighters	:	Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
Fire and explosion conditions	:	This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Transfer to appropriate container for disposal. Stop flow. Contain spill. Keep out of water courses. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal. Use appropriate protective equipment. Avoid contact with material.

SECTION 7 - HANDLING AND STORAGE

Handle in compliance with common hygienic practices. Clean hands thoroughly after handling. Keep from freezing. Do not use in confined or poorly ventilated areas. Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Store in sealed containers in a dry, ventilated warehouse location above freezing.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**Personal protection equipment**

Respiratory protection	:	Not required under normal conditions of use. Wear appropriate, NIOSH/MSHA approved respirator with combination particulate filter and vapor/gas removing cartridge when the ventilation is not adequate or if it is necessary to abrade or grind surfaces coated with this product.
Hand protection	:	Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
Eye protection	:	Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily

**SUPER DIAMOND CLEAR VOX LOW VOC**

Version 2.0

Print Date 04/24/2013

REVISION DATE: 02/08/2013

available.

- Skin and body protection : Prevent contact with shoes and clothing. Use rubber apron and overshoes.
- Protective measures : Other equipment not normally required. Use professional judgment in the selection, care, and use.
- Engineering measures : Not required under normal conditions of use. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

No known components with exposure limits.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Form : Liquid
- Color : White
- pH : 8.95
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : Not available.
- Water solubility : Soluble
- Specific Gravity : 1.009
- % Volatile Weight : 74.2 %

SECTION 10 - REACTIVITY / STABILITY

- Substances to avoid : Strong acids. Strong bases.
- Stability : Stable
- Hazardous polymerization : Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Glycol ether solvent, CAS-No.: 112-34-5

Acute oral toxicity (LD-50 oral)

6,560 mg/kg (Rat) 2,000 mg/kg (Guinea pig) 2,200 mg/kg
(Rabbit)



SUPER DIAMOND CLEAR VOX LOW VOC

Version 2.0
REVISION DATE: 02/08/2013

Print Date 04/24/2013

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Dispose of in compliance with state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

CFR / DOT:

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components : Glycol ether solvent 112-34-5

SARA 311/312 Hazards : Acute Health Hazard

OSHA Hazardous Components :
Glycol ether solvent 112-34-5

OSHA Status: Considered : Irritant
hazardous based on the
following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and : 96 g/l
exempt solvent)

VOC Method 310 : 2 %

U.S. State Regulations:



SUPER DIAMOND CLEAR VOX LOW VOC

Version 2.0

Print Date 04/24/2013

REVISION DATE: 02/08/2013

MASS RTK Components	:	Ammonia	7664-41-7
Penn RTK Components	:	Water	7732-18-5
		Styrene-Acrylic Polymer	NJ TSRN# 51721300-6336P
		Glycol ether solvent	112-34-5
NJ RTK Components	:	Water	7732-18-5
		Styrene-Acrylic Polymer	NJ TSRN# 51721300-6336P
		Glycol ether solvent	112-34-5
		Dipropylene glycol dibenzoate	27138-31-4

Components under California Proposition 65:
None known.

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	1
Flammability	0
Reactivity	0
PPE	

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

- ACGIH - American Conference of Governmental Hygienists
- CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
- DOT - Department of Transportation
- DSL - Domestic Substance List
- EPA - Environmental Protection Agency
- HMIS - Hazardous Materials Information System
- IARC - International Agency for Research on Cancer
- MSHA - Mine Safety Health Administration
- NDSL - Non-Domestic Substance List
- NIOSH - National Institute for Occupational Safety and Health
- NTP - National Toxicology Program
- OSHA - Occupational Safety and Health Administration
- PEL - Permissible Exposure Limit
- RCRA - Resource Conservation and Recovery Act
- RTK - Right To Know
- SARA - Superfund Amendments and Reauthorization Act
- STEL - Short Term Exposure Limit
- TLV - Threshold Limit Value
- TSCA - Toxic Substances Control Act
- TWA - Time Weighted Average
- V - Volume
- VOC - Volatile Organic Compound
- WHMIS - Workplace Hazardous Materials Information System