

TECHNICAL DATA SHEET

DESCRIPTION

A3 Standard Snap Tie is manufactured with either hot or cold forged integral heads and is equipped with flats or crimps to prevent turning in the concrete during breakback operations. Coating the tie with wax will aid in breakback operation.

APPLICATION

Used for handset wood wall forming.



FEATURES

- 2,250 lbs. SWL
- Available in any length from 6" to 480"
- Available with plastic cone, metal cone, metal spreader, flat fixed washer or cupped loose washer
- Can be manufactured with a tight fitting neoprene washer located near the center of tie to eliminate water seepage along the tie
- A3 Stainless Steel Snap Ties are available for applications that require ties resistant to rusting or other similar corrosion

INSTALLATION

1. Drill holes in plywood 1/8" larger than the snap tie head (usually 5/8" diameter drill bit will be required)
2. Place the ends of snap ties through the holes in the plywood
3. Place the bracket (Jahn® "A", Jahn® "C" or Omni wedge) on the tie
4. The proper tie head position is at the midpoint or higher of the Omni wedge slot. Correct spacing between double wales is 5/8" to 3/4"
5. Jahn® "A" bracket is utilized to hold a single wale and can be installed before or after the wales have been positioned

RELATED PRODUCTS

- A2 Plastic Cone
- A16 Omni Wedge
- A81 Jahn® "A" Bracket
- A82 Jahn® "C" Bracket

ORDERING INFORMATION

LOOSE WASHER OR 1" X 1" PLASTIC CONE

Product Code	Description	Weight
N/A	TO 8" X 4-3/4" L&W	0.247 LB
N/A	OVER 8" TO 10" X 4-3/4" L&W	0.269 LB
N/A	OVER 10" TO 12" X 4-3/4" L&W	0.291 LB
N/A	OVER 12" TO 13" X 4-3/4" L&W	0.302 LB
N/A	OVER 13" TO 14" X 4-3/4" L&W	0.313 LB
N/A	OVER 14" TO 15" X 4-3/4" L&W	0.324 LB
N/A	OVER 15" TO 16" X 4-3/4" L&W	0.335 LB
N/A	OVER 16" TO 17" X 4-3/4" L&W	0.346 LB
N/A	OVER 17" TO 18" X 4-3/4" L&W	0.357 LB
N/A	OVER 18" TO 19" X 4-3/4" L&W	0.368 LB
N/A	OVER 19" TO 20" X 4-3/4" L&W	0.380 LB
N/A	OVER 20" TO 21" X 4-3/4" L&W	0.391 LB
N/A	OVER 21" TO 22" X 4-3/4" L&W	0.402 LB
N/A	OVER 22" TO 23" X 4-3/4" L&W	0.413 LB
N/A	OVER 23" TO 24" X 4-3/4" L&W	0.425 LB
N/A	FOR EACH 1" OR FRACTION OVER 24" TO 144"	0.011 LB
N/A	TO 8" X 8-1/4" L&W	0.340 LB
N/A	OVER 8" TO 10" X 8-1/4" L&W	0.363 LB
N/A	OVER 10" TO 12" X 8-1/4" L&W	0.385 LB
N/A	OVER 12" TO 13" X 8-1/4" L&W	0.390 LB
N/A	OVER 13" TO 14" X 8-1/4" L&W	0.401 LB
N/A	OVER 14" TO 15" X 8-1/4" L&W	0.412 LB
N/A	OVER 15" TO 16" X 8-1/4" L&W	0.423 LB
N/A	OVER 16" TO 17" X 8-1/4" L&W	0.434 LB
N/A	OVER 17" TO 18" X 8-1/4" L&W	0.445 LB
N/A	OVER 18" TO 19" X 8-1/4" L&W	0.466 LB
N/A	OVER 19" TO 20" X 8-1/4" L&W	0.477 LB
N/A	OVER 20" TO 21" X 8-1/4" L&W	0.499 LB
N/A	OVER 21" TO 22" X 8-1/4" L&W	0.500 LB
N/A	OVER 22" TO 23" X 8-1/4" L&W	0.510 LB
N/A	OVER 23" TO 24" X 8-1/4" L&W	0.521 LB
N/A	FOR EACH 1" OR FRACTION OVER 24" TO 144"	0.011 LB

MANUFACTURER

Dayton Superior Corporation
 1125 Byers Road
 Miamisburg, OH 45342
 Customer Service: 888-977-9600
 Technical Services: 877-266-7732
 Website: www.daytonsuperior.com

TECHNICAL DATA SHEET**WARRANTY (ACCESSORIES)**

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.