

## CEILING FLANGE & CONCRETE INSERT

## Fig. 940, 941, & 942 CEILING FLANGE

Fig. 940 PLAIN

Fig. 941 ELECTRO-GALVANIZED

Fig. 942 COPPER COLOR EPOXY FINISH

**FUNCTION:** Designed to provide a means for attaching hanger rod to wood


beams or ceilings.

APPROVALS: Underwriters Laboratories Listed in the U.S. (UL) and Canada

(CUL) for supporting up to 2" (50) pipe max. (38 " rod size only).

**MATERIAL:** Malleable iron or Low carbon steel

**ORDERING:** Specify thread size and figure number.



Rod											Max. Rec. Load		Wt. Each	
Size A	В		С		D		E		F		lbs.	Kn	lbs.	kg
* <sup>3</sup> / <sub>8</sub>	$2^{3}/_{4}$	(69.85)	2	(50.8)	1/2	(12.7)	<sup>5</sup> / <sub>16</sub>	(7.94)	$1^{3}/_{8}$	(34.93)	180	(8.0)	.18	(.08)
1/2	$2^{3}/_{4}$	(69.85)	2	(50.8)	1/2	(12.7)	<sup>5</sup> / <sub>16</sub>	(7.94)	1 <sup>3</sup> / <sub>8</sub>	(34.93)	180	(8.0)	.18	(.08)

\*Available in stainless steel. To order, specify 304 or 316 and add suffix SS to figure number. Price on request.

Unless otherwise specified, all dimensions on drawings and in charts are in inches and dimensions shown in parentheses are in millimeters.