



ROLAIR STANDARD FEATURES

- PUMP:** ROLAIR Quality, Single Stage, Ball Bearings, Cast-Iron Cylinder, Stainless Steel Reed Valves and Splash Lubrication Ensure Longer Life.
- MOTOR:** 2 HP, 3400 RPM, Low Amp Draw, Overload Protection with Manual Reset, 115 Volt, 60 Hz, Heavy-Duty/Industrial Grade with Ball Bearings for Greater Durability.

SPECIFICATIONS

MODEL	MOTOR HP	# OF CYLS.	CU.FT. DISPLACED	CU.FT. FREE AIR@100 PSI	TANK CAP. (GAL.)	DIMENSIONS (L X W X H)	APPROX. SHIPPING WEIGHT
FC2002	2	1	7.8	4.0	4.3	20" x 15" x 17"	62 lbs.

STANDARD EQUIPMENT

- Start/Stop Pressure Switch with On/Off Lever
- Air Line Regulator and Pressure Gauge
- Low Profile Stack Tank
- Tank Pressure Gauge
- Safety Relief Valve
- Intake Filter Silencer
- 14.2 Amp Motor
- Initial 12 oz Oil Fill Included



ROLAIR SYSTEMS

606 S. LAKE ST, P O BOX 346, HUSTISFORD WI 53034-0346
SALES FAX: 920.349.3691 - SERVICE FAX: 920.349.8861
PHONE: 920-349-3281

www.rolair.com



ROLAIR STANDARD FEATURES

PUMP: ROLAIR Quality, Single Stage, Ball Bearings, Cast-Iron Cylinder, Stainless Steel Reed Valves and Splash Lubrication Ensure Longer Life.

MOTOR: 2 HP, 3400 RPM, Low Amp Draw, Overload Protection with Manual Reset, 115 Volt, 60 Hz, Heavy-Duty/Industrial Grade with Ball Bearings for Greater Durability.

SPECIFICATIONS

MODEL	MOTOR HP	# OF CYLS.	CU.FT. DISPLACED	CU.FT. FREE AIR@100 PSI	TANK CAP. (GAL.)	DIMENSIONS (L X W X H)	APPROX. SHIPPING WEIGHT
FC2002HBP6	2	1	7.8	4.0	5.3	16" x 14" x 31"	43 lbs.

STANDARD EQUIPMENT

- Start/Stop Pressure Switch with On/Off Lever
- Air Line Regulator and Pressure Gauge
- Dolly-Cart with Wheels for Easy Maneuvering
- Tank Pressure Gauge
- Safety Relief Valve
- Intake Filter Silencer
- 14.2 Amp Motor
- Initial 12 oz. Oil Fill Included



ROLAIR SYSTEMS

606 S. LAKE ST, P O BOX 346, HUSTISFORD WI 53034-0346
SALES FAX: 920.349.3691 - SERVICE FAX: 920.349.8861
PHONE: 920-349-3281

www.rolair.com