

FinishPro®42XP

15 Ga. 34° Finish Nailer

The FinishPro 42XP has established itself as the marquee tool for professional finish carpenters. The FinishPro 42XP has great durability and superior performance.



Applications

Baseboards, cabinets, case goods, caskets, chair rails, decorative trim, door & window casing, sash & millwork, exterior trim, finish applications/trim, furniture and paneling.

Features and Benefits

- Five year limited warranty
- Rugged internal engine design
- NeverLube® technology no lubrication required
- Magnesium housing lightweight and comfortable to use all day
- Thumb wheel adjustable depth-of-drive
- Comfort grip
- EZ-Clear™ latch to clear jams fast
- 360° adjustable exhaust
- Two No-Mar pads with onboard storage to protect work materials
- Advanced belt hook convenient storage

Specifications

Item# 4G0001N

Sequential Actuation

Reg. Operating Pressure 70-120 psi (4.8 - 8.3 bar)

Air Consumption (60 cycles per min.) .. 3.87 scfm Air Inlet 1/4" NPT Tool Weight 4.7 lbs (2.1 kg) Width 3.5" (89 mm)

Fastener Capacity 104



Fastener Specifications

Finish Bright Basic, Galv. & Stainless Collation 34° angles mylar taped strip

15 Ga. 34° Angled Strip Finish Nails

Length	Item Code	Count	Point	Finish	Package
11⁄4	DA15EPBN	4.M	Chisel	Bright	Box
11/2	DA17EPBN	4.M	Chisel	Bright	Вох
13/4	DA19EPBN	4.M	Chisel	Bright	Box
2	DA21EPBN	4.M	Chisel	Bright	Box
21/4	DA23EPBN	4.M	Chisel	Bright	Box
21/2	DA25EPB	3.M	Chisel	Bright	Box
1½	A301500	0.7M	Chisel	Bright	Clamshell
1¾	A301750	0.7M	Chisel	Bright	Clamshell
2	A302000	0.7M	Chisel	Bright	Clamshell
21/2	A302500	0.7M	Chisel	Bright	Clamshell
11⁄4	DA15EABN	4.M	Chisel	Galv	Box
11/2	DA17EABN	4.M	Chisel	Galv	Box
1¾	DA19EABN	4.M	Chisel	Galv	Box
2	DA21EABN	4.M	Chisel	Galv	Box
21/2	DA25EAB	3.M	Chisel	Galv	Вох
2	A302009	0.7M	Chisel	Galv	Clamshell
21/2	A302509	0.7M	Chisel	Galv	Clamshell
2	DA21EGBN	2.M	Chisel	Stainless	Box
21/2	DA25EGB	1.2M	Chisel	Stainless	Box
	Reg. Galv Heat Treated*				
11/2	DA17AIA	4.M	Diamond	Hardened*	Box
1¾	DA19AIA	4.M	Diamond	Hardened*	Вох
13/4	DA19AIA	4.M	Diamond	Hardened*	Box

^{*}Hardened 15 gauge for steel stud and trim application



FinishPro®42XP

15 Ga. 34° Finish Nailer **Features**



*Choose the right actuation mode!

Sequential Actuation (also known as restrictive trigger or trigger fire) operates in the following a sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tool to ensure proper use and safety precautions. For additional information on trigger systems and how SENCO will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: www.senco.com