



MODEL FC250090L

2 HP SINGLE-STAGE, DIRECT-DRIVE
WORKSHOP AIR COMPRESSOR

New Pump!
22% More Air!



Newly Redesigned Handle WITH Manifold!



ROLAIR STANDARD FEATURES

- PUMP:** ROLAIR Quality, Single Stage, Ball Bearings, Cast-Iron Cylinder, Stainless-Steel Reed Valves and Splash Lubrication Ensure Longer Life.
- MOTOR:** 2 HP, 3400 RPM, S-1 Rated for Continuous Duty, Low-Amp Draw, Overload Protection with Manual Reset, 115 Volt, 60 Hz, Heavy-Duty/Industrial-Grade with Ball Bearings for Greater Durability.

SPECIFICATIONS

MODEL	MOTOR HP	# OF CYLS.	CU. FT. DISPLACED	CU. FT. DELIVERED @ 90 PSI	TANK CAP. (GAL.)	DIMENSIONS (L X W X H) (INCHES)	APPROX SHIPPING WT. (LB.)
FC250090L	2	1	10.1	5.1	24	23 X 28 X 44	160

STANDARD EQUIPMENT

- Start/Stop Pressure Switch
- Air Line Regulator and Pressure Gauge
- Tank Pressure Gauge
- Easy-To-Maneuver 24-Gallon Tank
- Wheels and Handle
- Safety Relief Valve
- Intake Filter Silencer
- Initial 12 oz. Oil Fill Included
- Manual Tank Drain



606 South Lake Street > P.O. Box 346 > Hustisford, WI 53034-0346 > 920.349.3281 > fax 920.349.3691 > www.rolair.com

