



ROLAIR STANDARD FEATURES

PUMP: ROLAIR Quality, Single Stage, Ball Bearings, Cast-Iron Cylinder, Stainless-Steel Reed Valves and Splash Lubrication Ensure Longer Life.

MOTOR: 2.5 HP, 3400 RPM, S-1 Rated for Continuous Duty, Low-Amp Draw, Overload Protection with Manual Reset, 115 Volt, 60 Hz, Heavy-Duty/Industrial-Grade with Ball Bearings for Greater Durability.

SPECIFICATIONS

MODEL	MOTOR HP	# OF CYLS.	CU. FT. DISPLACED	CU. FT. DELIVERED @ 90 PSI	TANK CAP. (GAL.)	DIMENSIONS (L X W X H) (INCHES)	APPROX. SHIPPING WT. (LB.)
VT25BIG	2.5	1	9.3	6.5	5.3	30 x 21 x 20 (handle down)	108

STANDARD EQUIPMENT

- 100% Duty-Cycle Motor
- Start/Stop Pressure Switch with On/Off Lever
- Fold-Down Handle for Easy Storage, Low Profile
- Heavy-Duty Wheels for Greater Jobsite Mobility
- User-Friendly Control Panel Including Gauges, Two Quick-Disconnect Couplers and Air Regulator
- Safety-Relief Valve
- Intake Filter Silencer
- 13.8 Amp Motor
- Initial 10 oz. Oil Fill Included
- Built-In Power Cord Wrap

