

Reciprocating Blades

Reciprocating Blades



Diamond® Recip Blades

- Nickel alloy-brazed diamond particles maintain sharpness to last three times longer
- Narrow kerf design enables thinner, faster cuts
- Cuts cast iron, tile, brick and architectural stone
- One blade per pack



Item #	Code	Length x Width x Thickness (inches)	Stock*
10833	LEN	8 x 3/4 x .040	Y



Master-Grit® Recip Blades

- Tungsten carbide, medium grit edge
- Specially designed for cutting tough abrasives, such as cast iron, fiberglass, ceramic wall tile, clay pipe, stone, brick, plaster and marble
- Two blades per pack

Item #	Code	Length x Width x Thickness (inches)	Stock*
600RG	LEN	6 x 3/4 x .032	Y
800RG	LEN	8 x 3/4 x .040	Y
20506-100RG	LEN	10 x 3/4 x .050	A



Gold® Recip Blades

- Reinforced tooth design and precision applied titanium coating dissipate heat
- Bi-metal design
- Five blades per pack

Item #	Code	Length x Width x Thickness (inches)	Teeth Per Inch	Application	Stock*
21060	LEN	6 x 3/4 x .050	6	Wood	Y
21062	LEN	12 x 3/4 x .050	6	Wood	Y
21067	LEN	9 x 3/4 x .050	14	Metal	Y
21069	LEN	6 x 7/16 x .050	18	Metal	Y
21070	LEN	6 x 3/4 x .035	18	Metal	Y

*Y = stock item; A = readily available by order

Reciprocating Blades



LENOX®

Item #	Code	Length x Width x Thickness (inches)	Teeth Per Inch	Qty. Per Packt	Stock*	Application
656R	LEN	6 x 3/4 x .050	6	5	Y	Roughing-in work & nail-embedded wood. Fast cutting.
156R	LEN	12 x 3/4 x .050	6	5	Y	Pipe, structural steel, stainless steel, nonferrous metal: 3/16" & thicker.
956R	LEN	9 x 3/4 x .050	6	5	Y	
676RC	LEN	6 x 7/16 x .050	6	5	Y	Contour cutting in all wood, nail-embedded wood & composition materials.
606R	LEN	6 x 3/4 x .035	6	5	Y	Fast cutting for wood, composition materials, plastics & nonferrous metal.
634R	LEN	6 x 3/4 x .050	4	5	Y	Extra fast cutting in thick, nail-free wood.
610R	LEN	6 x 3/4 x .035	10**	5	Y	Nail-embedded wood, composition materials & plastic.
810R	LEN	8 x 3/4 x .050	10**	5	Y	Pipe, carbon steel & stainless steel: 3/8" - 1/4" thick.
110R	LEN	12 x 3/4 x .050	10/14**	5	Y	Nonferrous metal: 1/8" - 1/2" thick.
20520-314RC	LEN	3 5/8 x 5/16	14**	5	A	Contour cutting in wood less than 3/4" thick & in metal 3/32" - 5/16" thick.
20550-414R	LEN	4 x 3/4 x .035	14**	5	A	Pipe, structural steel, stainless steel: 3/32" - 1/4" thick.
614R**	LEN	6 x 3/4 x .035	14**	5	Y	Nonferrous metal: 3/32" - 3/8". Hard rubber.
418R**	LEN	4 x 3/4 x .035	18**	5	Y	
618R**	LEN	6 x 3/4 x .035	18**	5	Y	Structural steel, pipe, conduit, stainless steel:
818R**	LEN	8 x 3/4 x .035	18**	5	Y	1/16" - 5/16" thick. Nonferrous metal: 1/16" - 5/16" thick.
20510-118R	LEN	12 x 3/4 x .035	18**	5	A	
318RC**	LEN	3 5/8 x 9/16 x .035	18**	5	Y	Contour cutting in metal: 1/16" - 1/8" thick.
20554-424R	LEN	4 x 3/4 x .035	24**	5	A	
624R**	LEN	6 x 3/4 x .035	24**	5	Y	All metals less than 1/8" thick. Tubing, conduit & trim.
20579-824R	LEN	8 x 3/4 x .035	24**	5	A	
20449-456RP	LEN	4 x 3/4 x .050	6	5	A	For plaster, plaster board and lath. Bi-directional cutting.
636RP	LEN	6 x 3/4 x .050	6	5	Y	
6066R	LEN	6 x 7/8 x .062	6	2	Y	Demolition work in nail-embedded wood.
966R	LEN	9 x 7/8 x .062	6	2	Y	
960R**	LEN	9 x 7/8 x .062	10**	2	Y	Demolition work in wood and metal. Fire and rescue.
20500-106R	LEN	12 x 7/8 x .062	6	2	A	
650R	LEN	6 x 3/4 x .050	10/14	2	Y	
20577-850R	LEN	8 x 3/4 x .050	10/14	5	A	Heavy-duty. Extended life when cutting pipe, structural steel and stainless steel. Fire and rescue.
20593-6514R	LEN	6 x 3/4 x .050	14**	2	A	Stainless steel: 3/32" - 3/8" thick.
20594-6518R	LEN	6 x 3/4 x .050	18**	2	A	Stainless steel: 1/16" - 1/4" thick.
20511-9514R	LEN	9 x 3/4 x .050	14**	2	A	Stainless steel: 3/32" - 3/8" thick.

**Tuff Tooth™ design

*Available in 25-packs; use "B" as prefix to Item #

20572-656R



20556-676RC



20560-606R



20575-634R



20562-610R



20550-414R



20552-418R



20521-318RC



20554-424R



20449-456RP



20512-6066R



20597-960R



20592-650R



20511-9514R



*Y = stock item; A = readily available by order

Utica 315-724-7119

Watertown 315-788-2612

Syracuse 315-671-4400